Exposure Scenario (ES) for Use 1: "Chemical conversion coating using chromium trioxide, sodium dichromate, potassium dichromate, and/or dichromium tris(chromate) in aerospace and defence industry and its supply chains"

ECS and WCS	Task (ERC/ spERC or PROC)	Annual amount per site (kg Cr(VI)/ year)	Technical RMMs, including: *Containment, *Ventilation (general, LEV) *customized technical installation, etc.	Organisational RMMs, including: *Duration and Frequency of exposure *OSH management system *Supervision *Monitoring arrangements *Training, etc.	PPE (characte- ristics)	Other conditions	Effective- ness of waste water and waste air treat- ment (for ERC)	Release factors: water, air and soil (for ERC)	Detailed info. in CSR (section)
ECS 1	ERC 5	0 - 332	 Air: Chemical treatment baths equipped with LEV Air abatement by wet scrubber or air filters ^a Wastewater: Either sent to certified company for disposal (with or without prior recycling and evaporation) of liquid hazardous waste, or recycled after evaporation and/or treated onsite by reduction (reduced wastewater sent to external STP or WWTP) Soil: Indoor and outdoor surfaces where chemicals are handled are sealed Tanks are surrounded by secondary containment pits Waste: Solid Cr(VI) waste collected, stored in closed containers and forwarded to certified external company 	 Up to 365 days/year Emissions to air and water monitored regularly 	n.a.	Air: - Process temperature of treatment baths: (RT - 105°C) Water: - STP removal rate: 50% to sludge assumed	n.a.	Air: 0.00001 - 43.1 kg/a ^b Water: 0 - 3.57 kg/a ^b Soil: 0 kg/a (no release to soil)	Section 9.2.3.1

WCS 1 -	PROC 9,	n.a.	- Surface treatment by	- Duration and frequency task-	- Gloves ^c	- Up to	n.a.	n.a.	9.2.3.2
Line	PROC 13,		dipping/immersion and	dependent		14.6%			
operators	PROC 28		sampling of treatment		- RPE ^d	Cr(VI)			
			baths: with LEV	- Duration: <1 – 150 min/task/					
				shift (less for automated lines;	- Eye	- Indoors			
			- Surface treatment by filling	1x/month cleaning up to 180 min	protection				
			of parts under mechanical	is required)		- RT –			
			ventilation, otherwise		- Chemical	105°C			
			natural ventilation	 Frequency: 1 – 240 days/task/ 	protective				
				year	clothing, for				
				·	cleaning with				
				Advanced occupational health and	hose apron				
				safety management system:	and				
				- Regular exposure monitoring	waterproof				
				- Workers' training	boots				
				- Instructions available at					
				workplaces					
				- PPE management system					
				- Chemical products stored in					
				designated area					
				- Effective cleaning practices					
				implemented to prevent surface					
				contamination in vicinity of tanks					
				- Inspection and maintenance of					
				•					
				LEV					

WCS 2 -	PROC 9,	n.a.	- Solution preparation for	- Duration and frequency task-	- Gloves ^c	- Up to 52%	n.a.	n.a.	9.2.3.3
Brush and	PROC 10		brush or swab application :	dependent		Cr(VI)			
pen			with LEV		- RPE ^d				
application				- Duration: <1 – 60 min/task/	_	- Indoors			
operators			- Natural ventilation	shift	- Eye	DT			
				- Frequency: <1 – 240 days/task/	protection	- RT			
				year	- Chemical				
				year	protective				
				Advanced occupational health and	clothing, for				
				safety management system:	cleaning with				
				- Regular exposure monitoring	hose apron				
				- Workers' training	and				
				- Instructions available at	waterproof				
				workplaces - PPE management system	boots				
				- Chemical products stored in					
				designated area					
				- Effective cleaning practices					
				implemented to prevent surface					
				contamination in vicinity of tanks					
				- Inspection and maintenance of					
				LEV					0 2 2 4
WCS 3 - Storage	PROC 5 PROC 8b,	n.a.	 Bath make-up or addition: with LEV 	 Duration and frequency task- dependent 	- Gloves ^c	- Up to 52% Cr(VI)	n.a.	n.a.	9.2.3.4
area	PROC 28			dependent	- RPE is used				
workers	11100 20		- Natural ventilation	- Duration: <1 – 60 min/task/shift		- Indoors			
				,,.	and weighing				
				- Frequency: <1 – 240 days/task/	of solids and	- RT – 45°C			
				year	for bath				
					emptying and				
				Advanced occupational health and	cleaning ^d				
				safety management system: - Regular exposure monitoring	- Eye				
				- Workers' training	protection				
				- Instructions available at	F				
				workplaces	- Chemical				
				- PPE management system	protective				
				- Chemical products stored in	clothing, for				
				designated area	cleaning with				
				- Effective cleaning practices implemented to prevent surface	hose apron and				
				contamination in vicinity of tanks	waterproof				
						1	1	1	1
				- Inspection and maintenance of	boots				

				Area in which activities involving the use of solids chromates are conducted is restricted physically by means of barriers or by means of a strict procedure					
WCS 4 - Laboratory technicians	PROC 15	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	9.2.3.5
WCS 5 - Maintenance and/or cleaning workers	PROC 28	n.a.	- Natural ventilation	 Duration: up to 240 min/shift (at some sites, specific maintenance activities are performed for 480 min once per year) Frequency: 48 days/year Advanced occupational health and safety management system: Regular exposure monitoring Workers' training Instructions available at workplaces PPE management system Effective cleaning practices implemented to prevent surface contamination in vicinity of tanks 	- Gloves ^c - RPE ^d - Eye protection - Chemical protective clothing	- Up to 14.6% Cr(VI) - Indoors - RT	n.a.	n.a.	9.2.3.6
WCS 6 - Machinists	PROC 21, PROC 24	n.a.	- Mechanical ventilation, where technically feasible	 Duration: up to 180 min/shift (at few sites infrequent long-term activities of up to 600 min/ shift on 2 days per year) Frequency: <1 - 240 days/year Advanced occupational health and safety management system: Regular exposure monitoring Workers' training Instructions available at workplaces PPE management system Effective cleaning practices implemented to prevent surface contamination in vicinity of tanks 	- RPE ^d - Eye protection - Protective suit	- Indoors - RT	n.a.	n.a.	9.2.3.7

WCS 7 -	PROC 0	n.a.	- Natural ventilation	- Duration: up to 480 min/shift	- Standard	- Up to	n.a.	n.a.	9.2.3.8
Incidentally					PPE	14.6%			
exposed workers				- Frequency: 240 days/year		Cr(VI)			
				Advanced occupational health and		- Indoors			
				safety management system:					
				- Workers' training		- RT			
				- Instructions available at					
				workplaces					
				 PPE management system Effective cleaning practices 					
				implemented to prevent surface					
				contamination in vicinity of tanks					

Notes:

^a For operations where exposure potential is low (i.e. operations are infrequent using only small quantities of Cr(VI)), air emission abatement may not be required.

^b Total release per site of sites performing this use, with only a certain share generated by this use.

^c Gloves (tested to EN374), material and thickness depending on task, see WCS 1 - 4.

^d RPE according to EN 529:2005 is worn during all tasks involving solid chromates (measuring and weighing of solids and for bath emptying and cleaning) and for all tasks not performed under LEV for which industrial hygiene exposure assessment confirms RPE use is required: Half mask FFP3, half mask with P3 filter/P3 combination filter or full mask with P3 filter/P3 combination filter.

Abbreviations: WCS=Worker contributing scenario, ECS=Environmental Contributing Scenario, ERC=Environmental Release Category, STP=Sewage Treatment Plant, WWTP=Wastewater Treatment Plant, PROC=Process category, LEV=Local Exhaust Ventilation, PPE=Personal Protective Equipment, RPE=Respiratory Protective Equipment, RT=Room temperature, n.a.= not applicable