<u>Exposure Scenario (ES) for Use 1:</u> "Passivation of (non-AI) metallic coatings using chromium trioxide or sodium dichromate or potassium dichromate in aerospace and defence industry and its supply chains"

ECS and WCS	Task (ERC/ spERC or PROC)	Annual amount per site (kg Cr(VI)/ year)	Technical RMMs, including: *Containment, *Ventilation (general, LEV) *customized technical installation, etc	Organisational RMMs, including: *Duration and Frequency of exposure *OSH management system *Supervision *Monitoring arrangements *Training, etc	PPE (characte- ristics)	Other condition s	Effective- ness of waste water and waste air treat-ment (for ERC)	Release factors: water, air and soil (for ERC)	Detailed info. in CSR (section)
ECS 1	ERC 5	0.2 - 480	 Air: Chemical treatment baths equipped with LEV Air abatement by wet scrubbers or air filters a Wastewater: Either sent to certified company for disposal (with or without prior recycling and evaporation) of liquid hazardous waste, or recycled after evaporation and/or treated onsite by reduction (reduced wastewater sent to external STP or WWTP) Soil: Indoor and outdoor surfaces where chemicals are handled are sealed Tanks are surrounded by secondary containment pits Waste: Solid Cr(VI) waste collected and forwarded to certified external company 	- Up to 365 days/year - Emissions to air and water monitored regularly	n.a.	Air: - Process temperatu re of treatment baths: (10 - 70°C) Water: - STP removal rate: 50% to sludge assumed	n.a.	Air: 0.0192 - 43.1 kg/a b Water: 0 - 1.42 kg/a b Soil: 0 kg/a (no release to soil)	Section 9.2.3.1

WCS 1 - Line operators	PROC 9, PROC 10, PROC 13, PROC 28	n.a.	 Surface treatment by dipping/immersion, sampling of treatment baths and touch-up: with LEV Natural ventilation 	 Duration: <1 - 120 min/task/ shift (less for automated lines; 1x/month cleaning of up to 180 min is required) Frequency: 12 - 240 days/task/ year Advanced occupational health and safety management system: Regular exposure monitoring Workers' training Instructions available at workplaces PPE management system Chemical products stored in designated area Effective cleaning practices implemented to prevent surface contamination in vicinity of tanks Inspection and maintenance of LEV 	 Gloves ^c RPE ^d Eye protection Chemical protective clothing, for cleaning with hose apron and waterproof boots 	- Up to 8% Cr(VI) - Indoors - 10 – 70°C	n.a.	n.a.	9.2.3.2
WCS 2 - Storage area workers	PROC 5, PROC 8b, PROC 28	n.a.	- Bath make-up or addition: with LEV - Natural ventilation	 Duration and frequency task- dependent Duration: <1 - 60 min/task/shift Frequency: <1 - 240 days/task/ year Advanced occupational health and safety management system: Regular exposure monitoring Workers' training Instructions available at workplaces PPE management system Chemical products stored in designated area 	 Gloves ^c RPE is used for measuring and weighing of solids and for bath emptying and cleaning ^d Eye protection Chemical protective clothing, for cleaning with hose apron and waterproof boots 	- Up to 52% Cr(VI) - Indoors - RT – 45°C	n.a.	n.a.	9.2.3.3

WCS 3 - Laboratory technicians	PROC 15	n.a.	n.a.	 Effective cleaning practices implemented to prevent surface contamination in vicinity of tanks Inspection and maintenance of LEV n.a. 	n.a.	n.a.	n.a.	n.a.	9.2.3.4
WCS 4 - Maintenance and/or cleaning workers	PROC 28	n.a.	- Natural ventilation	 Duration: up to 240 min/shift (at some sites, specific maintenance activities are performed for 480 min once per year) Frequency: 48 days/year Advanced occupational health and safety management system: Regular exposure monitoring Workers' training Instructions available at workplaces PPE management system Effective cleaning practices implemented to prevent surface contamination in vicinity of tanks 	- Gloves ^c - RPE ^d - Eye protection - Chemical protective clothing	- Up to 8% Cr(VI) - Indoors - RT	n.a.	n.a.	9.2.3.5
WCS 5 - Machinists	PROC 21,24	n.a.	- Natural ventilation	 Duration: 10 – 90 min/shift (at few sites infrequent long- term activities of up to 600 min/ shift on 2 days per year) Frequency: 240 days/year Advanced occupational health and safety management system: Regular exposure monitoring Workers' training Instructions available at workplaces PPE management system Effective cleaning practices implemented to prevent surface contamination in vicinity of tanks 	- RPE ^d - Eye protection - Protective suit	- Indoors - RT	n.a.	n.a.	9.2.3.6

WCS 6 - Incidentally	PROC 0	n.a.	- Natural ventilation	- Duration: up to 480 min/shift	- Standard PPE	- Up to 8% Cr(VI)	n.a.	n.a.	9.2.3.7
exposed				 Frequency: 240 days/year 		. ,			
workers						- Indoors			
				Advanced occupational health					
				and safety management system:		- RT			
				 Workers' training 					
				 Instructions available at 					
				workplaces					
				 PPE management system 					
				 Effective cleaning practices 					
				implemented to prevent surface					
				contamination in vicinity of tanks					

Notes:

^a For operations where exposure potential is low (i.e. operations are infrequent using only small quantities of Cr(VI)), air emission abatement may not be required.

^b Total release per site of sites performing this use, with only a certain share generated by this use.

^c Gloves (tested to EN374), material and thickness depending on task, see WCS 1 - 4.

^d RPE according to EN 529:2005 is worn during all tasks involving solid chromates (measuring and weighing of solids and for bath emptying and cleaning) and for all tasks not performed under LEV for which industrial hygiene exposure assessment confirms RPE use is required: Half mask FFP3, half mask with P3 filter/P3 combination filter or full mask with P3 filter/P3 combination filter.

Abbreviations: WCS=Worker contributing scenario, ECS=Environmental Contributing Scenario, ERC=Environmental Release Category, STP=Sewage Treatment Plant, WWTP=Wastewater Treatment Plant, PROC=Process category, LEV=Local Exhaust Ventilation, PPE=Personal Protective Equipment, RPE=Respiratory Protective Equipment, RT=Room temperature, n.a.=not applicable